



CHASSIS® ADVANTAGE SPC PLUS

Classification	ASTM F-3261 Resilient flooring in modular format with Solid Polymeric Core
Size*	7" x 48" / 183 mm x 1220 mm
Overall Thickness*	0.18" / 4.5 mm (3.5 mm + 1 mm cushion backing) (nom)
Wear Layer	12 mil / 0.30 mm featuring Diff Shield MAX finish
Edge	Bevel
Standard Colors	8 colors
Installation Method	Angle/Angle
Wear Limited Warranty	30-Year Residential
Recycled Content	This product contains no recycled content.
Packaging	28.84 ft² (2.68 m²) per carton 12 pieces per carton 55 cartons per pallet
Weight Per Carton	42.88 lbs / 19.45 kg



Axle CAS-3815CB

PRODUCT TESTING

Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648	Class I, >1.13
Dimensional Stability	ASTM 2199	Passed
Residual Indentation	ASTM F 1914	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Smoke Density	ASTM E 662	Passed
Static Load Limit	ASTM F 970	Passed
Slip Resistance	ASTM C 1028	Passed
STC	ASTM E 90 / E 413	59
Delta IIC	ASTM E 2179	27



BEST | Wear Limited Warranty



CERTIFIED BY SCS Global Services



Axle CAS 3815CB



Clutch CAS 3816CB




Spitfire CAS 3807CB (Heavy Shade Variation)



Backbone Cas 3808CB (Heavy Shade Variation)




Caspas CAS 3801CB



Armature CAS 3802CB (Heavy Shade Variation)



Motorcoach CAS 3803CB



Suspension CAS 3804CB

*All measurements are nominal. Sound Testing will vary depending on the specific floor/ ceiling assembly.

Samples are intended to be a reference for product visuals and may not represent all color, shade, pattern, and texture variations. Actual product may differ from small swatches, printed media, or digital computer images.

Please visit www.earthwerks.com for full warranty details & installation guidelines. All specifications & offerings are subject to change without notice.