



## Addison Rigid Core Flooring

### Specification

Product name:	Addison
Floor type:	rigid core (SPC)
Structure:	5.0mm total thickness 3.7mm rigid core 0.3mm wear layer (12 mil) 1.0mm IXPE attached pad
Surface finish:	Wood grain finish with Enhanced Ceramic Bead coating for scratch and stain resistance
Bevel type:	Cut and Painted
Joint profile:	Licensed I4F - 3L Triplelock on short side, Angle Lock on long side
Installation:	Float, glue down
Plank size:	60" x 9"
Packaging:	6 pieces / carton 22.44 sf / carton 76 cartons / pallet 14 pallets / container 35 lbs / carton
Warranty:	Lifetime Residential 5 year Commercial

### Performance Specification:

Residual Indentation	ASTM F1914-07	Average $\leq$ 8% Maximum $\leq$ 8%	Surpasses requirements Surpasses requirements
Resistance to Chemicals	ASTM F925	No more than a slight change in dulling, surface attack, or staining	Pass
Dimensional Stability	ASTM F2199-09	$\leq$ 0.166%	Surpasses requirements
Static Load Limit	ASTM F970-17	$\leq$ 0.005"	Surpasses requirements
Residual Indentation	ASTM F1914-07	Average $\leq$ 8% Maximum $\leq$ 8%	Surpasses requirements
Coefficient of Friction	ASTM C1028-07	>0.6 wet and dry	Surpasses wet and dry
Resistance to Light	ASTM F1515-15	Average $\Delta E \leq$ 8.0	Surpasses requirements
Resistance to Heat	ASTM F1514-03	Average $\Delta E \leq$ 8.0	Surpasses requirements
Static Load	ASTM F970-17	$<$ 0.005" @ 250lbs load	Surpasses requirements
Heavy Metals	EN 71-3 Part3:1994		None detected
Phthalate content	CPSC-CH-C1001-09.3		None detected
Critical Radiant Flux	ASTM E648-17a	Class 1: $\geq$ 0.45 W/cm <sup>2</sup>	Surpasses requirements
Smoke Density	ASTM E662-17a		Surpasses requirements
Impact Sound (IIC)	ASTM E492-09	N/A	IIC = 60

Certifications: FloorScore, Greenguard Gold



REV: May 1, 2021