



PAVILION®

Classification	ASTM F 1700 Class III, type A or B Solid Vinyl Floor Tile
Size*	6" x 36" / 152.4 mm x 914.4 mm
Overall Thickness*	0.08" / 2.0 mm (nom)
Wear Layer	8 mil / 0.20 mm featuring Tuff Shield® finish
Edge	Square
Standard Colors	5 colors
Installation Method	Glue-Down
Wear Limited Warranty	20-Year Residential / 10-Year Light Commercial
Recycled Content	This product contains no recycled content.
Packaging	35.95 ft² (3.34 m²) per carton 24 pieces per carton 72 cartons per pallet
Weight Per Carton	26.50 lbs / 12.02 kg




Midtown SCP 1684

Product Testing


Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648-06	Class I, CRF ≥0.45
Dimensional Stability	ASTM F 2199	Passed
Flexibility	ASTM F 137	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Smoke Density	ASTM E 662-06	Passed
Static Load Limit	ASTM F 970	Passed
Thickness	ASTM F 386	Passed
STC Sound Testing	ASTM E 492-09	STC 61
IIC Sound Testing	ASTM E 989-06	IIC 64




BETTER I WEAR LIMITED WARRANTY




Tenement SCP 1681



Maisonette SCP 1683



Midtown SCP 1684



Park Place SCP 1685



Elevation SCP 1687

*All measurements are nominal. Sound Testing will vary depending on the specific floor/ ceiling assembly.

Samples are intended to be a reference for product visuals and may not represent all color, shade, pattern, and texture variations. Actual product may differ from small swatches, printed media, or digital computer images.

Please visit www.earthwerks.com for full warranty details & installation guidelines. All specifications & offerings are subject to change without notice.